

Low Pressure Nozzles

L O W P R E S S U R E N O Z Z L E S



ELKHART BRASS

For 1.5" & 1.75" Handlines



L-205-BA *
Mystery nozzle



LB-275-AF *
Mystery break-apart nozzle combination of L-205-BA and LB-275A ball shutoff...Base



4000-10 * *
CHIEF nozzle with integral standard ball shutoff... Base threads 1.5".



4000-13 * *
CHIEF nozzle with standard ball shutoff and rugged, cast pistol grip...Base threads 1.5".



4000-14 * * * *
CHIEF nozzle tip...Base threads 1.5".

4000-19 * *
CHIEF nozzle tip with twist shutoff...Base threads 1.5".

4000-18 * * * *
CHIEF break-apart nozzle combination of 4000-14 and LB-275GA ball shutoff...Base



Why Low Pressure Nozzles?

There are two ways to reduce reaction force on any handline nozzle....Either flow less water....Or lower the nozzle pressure. By reducing the flow, your fire-fighting capabilities are also diminished (water still extinguishes the fire)....However, by reducing the nozzle pressure to apply that flow, you merely lessen the reaction force of the fire stream....And that equates to less "wear-n-tear" on the nozzle team!

Mystery Nozzles

Constructed of durable, lightweight Elk-O-Lite with a heavy-duty protective EPDM bumper, these nozzles are ideal for Hi-Rise or street level operations. Like all Mystery nozzles, these feature excellent stream quality from full wide fog to a tight straight stream, with the capability of twisting the nozzle tip to complete shutoff. Any of these nozzles can be used with Elkhart's lightweight Elk-O-Lite ball shut-offs to make a variety of break-apart combinations. Refer to the color key on back page for optional flows.

Chief Nozzles

This single/constant gallonage series of nozzles features lightweight Elk-O-Lite construction with hard anodized finish; heavy-duty, protective, molded urethane bumpers; rugged aluminum/bronze shutoff handles with double stops; replaceable spinning teeth (molded rubber teeth optional on some models); flush without shutting down; and hydraulically balanced Acetal valve ball with adjustable, Teflon impregnated, neoprene seat. Chief nozzles are NFPA 1964 compliant. Refer to the color key on back page for optional flows.

For optional flows see color key on back page.



For 1.75" & 2" Handlines



4000-16 * * * *
CHIEF nozzle with midsize ball shutoff...Base threads 1.5".



* * * * **4000-17**
CHIEF nozzle with midsize ball shutoff and rugged, cast pistol grip...Base threads 1.5".



4000-20 * * * *
CHIEF nozzle with midsize ball shutoff and larger tip section



* * * * **4000-23**
CHIEF nozzle with midsize ball shutoff, larger tip section and rugged, cast pistol



4000-24 * * * *
CHIEF nozzle tip ...Base threads 1.5".
(Also available with twist shutoff)



* * * * **4000-31**
CHIEF break-apart nozzle combination of 4000-22 and B-275GAT midsize ball shutoff with built-in smooth bore tip...Base threads 1.5".



* * * **205-BA**
Mystery nozzle tip...
Base threads 1.5".



B-275-TAF *
Mystery nozzle break-apart combination of L-205-BA, 186A "Slug" tip and B-275A ball shutoff...Base threads 1.5".



* * * **B-275-GAT**
Mystery nozzle break-apart combination of 205-BA and B-275GAT midsize ball shutoff with built in smooth bore



SM-30FLP *
Select-O-Matic nozzle with midsize ball shutoff...Base threads 1.5".



* **SM-30GLP**
Select-O-Matic nozzle with midsize ball shutoff and rugged, cast pistol grip...Base threads



TSM-30FLP *
Select-O-Matic nozzle tip...Base threads 1.5".



* **STSM-30GLP**
Select-O-Matic break-apart nozzle combination of TSM-30FLP and B-275-GA midsize ball shutoff...Base

For optional flows see color key on back page.



More Low Pressure

For 2.5" & 3.0" Handlines



D-205-BA * * *
Mystery nozzle tip
...Base threads



4000-33 * * * * *
Chief nozzle for direct connect with pistol grip...Base



4000-26 * * * * *
Chief nozzle for direct connect ...Base threads 2.5".



4000-27 * * * * *
Chief nozzle break-apart combination of 4000-24 tip and B-278-L playpipe...Base



DB-275-GAF * * *
Mystery nozzle break-apart combination of 205-BA and DB-275-GA ball shutoff...Base threads 2.5".



DSM-30FGLP *
Select-O-Matic nozzle for direct connection with pistol grip...Base



JB-275-LAFD * * *
Mystery nozzle break-apart combination of D-205-BA and JB-275A ball shutoff...Base threads



DSM-30FLP *
Select-O-Matic nozzle for direct connection ...Base threads 2.5".



TSM-30BPALP *
Select-O-Matic nozzle break-apart combination of TSM-30FLP tip and B-

PICK YOUR FLOW & PRESSURE...

* 125 GPM @ 75psi	* 200 GPM @ 50psi
* 150 GPM @ 50psi	* 200 GPM @ 75psi
* 150 GPM @ 75psi	* 250 GPM @ 50psi
* 175 GPM @ 75psi	* 250 GPM @ 75psi
* 185 GPM @ 75psi	* 300 GPM @ 75psi
* 75-300 GPM @ 75psi	

...Then Choose The Nozzle That Fits The Need.

Elkhart Brass Mfg. Co., Inc.
Post Office Box 1127 ■ Elkhart, IN 46515
Telephone ■ (219) 295-8330
(800) 346-0250 ■ Fax: (219) 293-9914
Visit our web site at www.elkhartbrass.com

