

MANUAL EXTENDER™

**RAISE THE STREAM
CLEAR OBSTRUCTIONS
PROTECT THE RIG**

12" or 18" (305 mm or 457 mm) rise options

- Raises stream to prevent damage to apparatus equipment
- More ergonomic operating position

Monitor operates in raised or lowered position

- Full 360° rotation in either position

Automatically locks in up/down position

- Cannot be accidentally unlocked
- Prevents unintended extension under pressure
- Prevents unintended collapse when extended

Built-in sensor for connection to cab indicator light

- Notifies personnel when Extender is NOT stowed and locked

3" waterway

- Capable of 1250 gpm (4750 LPM) flow



Easy-op latch design for safe and simple deployment



Options:

MOUNTING OPTIONS

- Dual bracket
- Plate and saddle bracket

INLET OPTIONS

- 3" Victaulic
- 3" NPT
- 3" NPT with 150# Flange*

OUTLET OPTIONS

- 3" NPT
- 3" NPT with 150# Flange*

*Flange P/N 31030011 sold separately

ELKHART BRASS



SAFE  FLEET
Driving Safety Forward™

MANUAL EXTENDER™

ORDERING GUIDE

1

Select one of the Extender packages below

08599201 – 12" (305 mm)	08599211 – 12" (305 mm)	 <p>Dual Saddle Bracket</p>
08599001 – 18" (457 mm)	08599011 – 18" (457 mm)	
Manual Extender	Manual Extender	 <p>Plate and Saddle Bracket</p>
3" MNPT inlet	3" Victaulic inlet	
3" MNPT outlet	3" MNPT outlet	
Dual saddle brackets	Dual saddle brackets	
08599212 – 12" (305 mm)	08599213 – 12" (305 mm)	
08599012 – 18" (457 mm)	08599013 – 18" (457 mm)	
Manual Extender	Manual Extender	
3" MNPT inlet	3" Victaulic inlet	
3" MNPT outlet	3" MNPT outlet	
Plate and saddle bracket	Plate and saddle bracket	

2

Select monitor option (sold separately)

Recommended

- Stinger® 2.0 (deck mount)
- Stinger® 2.0 (portable)

See Stinger 2.0 selector guide for mounting connection options



Stinger 2.0

3

Select nozzle option (sold separately)

- SM-1000 2.5" Automatic nozzle
- SM-1250 2.5" Automatic nozzle
- 282A Stream Shaper (no charge when purchased with Stinger 2.0)
- Quad Stacked Tips (no charge when purchased with Stinger 2.0)



**SM Series
Automatic Nozzle**

This is intended as a guide only. For all options and configurations, please contact your Elkhart Brass Regional Sales Manager or Customer Service.

ELKHART  BRASS

04-22

Copyright ©2022 Safe Fleet and its subsidiaries. All rights reserved. No part of this publication may be reproduced by any means without written permission from Safe Fleet. The information in this publication is believed to be accurate. However, Safe Fleet does not make any representation or warranty to that effect and does not assume responsibility for any consequences resulting from use of such information. Revisions or new editions of the publication may be issued (or not issued) in our discretion to incorporate such changes.

+1 574-295-8330
elkhartbrass.com

SAFE  FLEET
Driving Safety Forward™