

PUSH/PULL DRAIN VALVE



110



115

Product Information	MODELS	
	110	115
Mounting	Direct	Panel
Inlet	0.75" NPT Female	
Outlet	.75" NPT Female	Male shank outlet for .75" ID drain hose
Handle length	2.25"	
Optional handle lengths	4.375", 3.0", or 1.5" (specify)	
Material	Cast brass valve body with stainless steel handle rod	
Additional features		Body pre-drilled for mounting

TWIST DRAIN VALVE



114

Product Information	MODELS	
	114A	114B
Mounting	Direct	Panel
Inlet	0.75" NPT Male	
Handle detail	Knurled	
Material	Elk-O-Lite® body with hard anodized finish	Cast brass body; finish — cast brass or chrome plating (specify)



116 QUARTER TURN DRAIN VALVE

- Panel mounted
- Body pre-drilled for mounting to pump panel
- Material: Cast brass valve body with stainless steel handle rod
- Inlet: 0.75" NPT
- Outlet: 0.75" NPT
- Machined brass ball
- Optional adapter with .125" NPT tap for gauge



MISCELLANEOUS APPARATUS

INLET SIZES							2.5" OUTLET OPTIONS				MATERIAL		DIMENSIONS		MODEL	FIGURE
Female	Male		2.5" Flange				NPT M F	Vic- taulic	NHT	Cast Brass	Elk-O Lite®	Length (Inches)	Weight (Lbs.)			
	2.5"	2.5"	3"	Ameri- can	Darley	Hale								Water- ous		
•							s			•		6.3	11.1	40-10	1	
			•		•	•	s		o	o	•		6.8	11.2	40-20	1
				•			s		o		•		6.1	11.1	40-22	1
	♥						s				•		6.8	10.9	40-32	2
	•						s		o		•		6.5	10.6	40-40	2
		•					s		o		•		6.1	10.9	40-41	2
•								s				•	6.3	3.5	40A	

KEY s = standard o = option
♥ NHT

40 RELIEF VALVE

- For use on the suction side of the pump or on a designated LDH discharge outlet
- Complies with NFPA 1901
- Material: Choice of cast brass or Elk-O-Lite® with stainless steel mechanism
- Rubber seat to ensure positive vacuum seal
- Adjustable psi of 75-250 (pre-set to 125 psi)

Figure 1



Fig. 1

Figure 2



Fig. 2

Figures depict general product types only and are not intended to be inclusive of all product features.



728 TANK FILL CHECK VALVE

- Eliminates the need for a quarter-turn ball valve
- Clapper retracts completely to produce a 3" waterway
- Seals quickly to prevent backflow
- Available in brass or Elk-O-Lite® (specify)
- Elk-O-Lite® version features NHT threads

THREADS

Inlet information is NHT and outlet information is NPT unless otherwise specified. See index T-12 for alternative thread options.