



5000E & SM-10FE

5000E & SM-10FE

- Created for the specific challenges, such as water flow limitations and protection needs, of wildland firefighting, dust abatement, de-icing, etc.
- Used in conjunction with smaller monitors such as the Sidewinder®
- Constant flow — straight stream, narrow fog (30°), or wide fog (90°) — with spinning teeth
- Either automatic or fixed flow nozzle type available
- Motor (12V or 24V DC available) totally enclosed and sealed
- Manual override standard
- Lightweight Elk-O-Lite® construction with hard anodized finish
- AFFF compatible



Base Size	AVAILABLE STANDARD FLOW RATES (Fixed) GPM (LPM)													STANDARD FLOW RANGE (Automatic) GPM (LPM)	TEETH		Effective Reach at Highest Flow (Ft.)	Weight (Lbs.)	MODEL	FIGURE	
	15 (57)	30 (114)	45 (170)	60 (227)	75 (284)	95 (360)	125 (473)	150 (568)	175 (662)	200 (757)	250 (946)	350 (1325)	400 (1514)		475 (1798)	Spinning					None
1.5"	PSI (BAR) 100 (6.89)													20 - 120 (76 - 454)	•		85	3.1	5000-04	2	
	•	•	•												•		124	3.1	5000-14	2	
				•	•	•				•	•	•	•		•	•		150	3.1	5000-24	2
																	•	115	4.9	SM-10FE*	1

* Suitable for de-icing / anti-icing use

5000E & SM10FE CONFIGURATIONS




Fig. 1

Fig. 2

OPTIONS
THREADS
<i>All nozzles are NHT unless otherwise specified. See index T-13 for optional base threads.</i>

Figures depict general product types only and are not intended to be inclusive of all product features.