

HANDLINE NOZZLES



CHIEF™

Chief™

Fixed flow Chief™ nozzles efficiently deliver a constant gallonage from straight stream to full fog. The simple rugged design makes the Chief™ easy to use, train with and reliable in tough situations. Superior hydraulics due to a fully machined waterway result in excellent stream quality and reach. The Chief™ is also available in true low pressure versions with specifically engineered, calibrated and labeled stems down to 50 psi. With more than 300 available variations the Chief™ is easily customized to meet your specific needs.

HANDLINE NOZZLES

1-3



British Standard Parallel Pipe (BSPP) and British Instantaneous (BS336) base options available.

HANDLINE NOZZLES

CHIEF™

HANDLINE NOZZLES

1-4

| BASE SIZE | PSI (BAR) | AVAILABLE STANDARD FLOW RATE GPM (LPM) | | | | | | | | | | | | | | BASE | | SHUT-OFF | HANDLE | TEETH | | | MODEL | | | | | | | | | | | | | |
|------------|------------|---|----------|----------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|-----------|------------|------------|------------|------------|----------|--------|-------|--------|-------------|-------|------|-------|-------|------|-----|-----------|------------------|-----------------|-----------|------|---------|---------|-----------|
| | | 15 (57) | 30 (114) | 45 (170) | 60 (227) | 75 (284) | 95 (360) | 125 (473) | 150 (568) | 175 (662) | 185 (700) | 200 (757) | 250 (946) | 275 (1041) | 300 (1136) | 325 (1230) | 350 (1325) | | | Rigid | Swivel | Free Swivel | | Long | Short | Twist | Ball | Tab | Horseshoe | Spinning Plastic | Molded Urethane | Cut Metal | | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | TYPE | LENGTH | | |
| 1" | 100 (6.89) | • | • | • | • | | | | | | | | | | | | | S | | | | | | | | | | | | | | | | | | 4000-04 |
| | 50 (3.45) | | | | | | | | | | | | | | | | | O | S | | | | | | | | | | | | | | | | | 4000-14 |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5" | 100 (6.89) | | | | • | • | • | • | • | • | • | • | • | • | • | • | • | | | | | | | | | | | | | | | | | | | |
| | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 100 (6.89) | | | | | | | | | | | | | | | | | S | | | | | | | | | | | | | | | | | | 4000-14HR |
| | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 75 (5.17) | | | | | | | | | | | | | | | | | O | S | | | | | | | | | | | | | | | | | 4000-19 |
| | 100 (6.89) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 50 (3.45) | | | | | | | | | | | | | | | | | O | S | | | | | | | | | | | | | | | | | 4000-22 |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 (6.89) | | | | | | | | | | | | | | | | | O | S | | | | | | | | | | | | | | | | | 4000-24 | |
| 2.5" | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 100 (6.89) | | | | | | | | | | | | | | | | S | | | | | | | | | | | | | | | | | | 4000-22 | |
| | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 (6.89) | | | | | | | | | | | | | | | | S | | | | | | | | | | | | | | | | | | 4000-24 | | |



Chief Tips

| BASE SIZE | PSI (BAR) | AVAILABLE STANDARD FLOW RATE GPM (LPM) | | | | | | | | | | | | | | BASE | | SHUT-OFF | HANDLE | TEETH | | | MODEL | | | | | | | | | | | | |
|------------|------------|---|----------|----------|----------|----------|----------|-----------|-----------|-----------|-----------|-----------|-----------|------------|------------|------------|------------|----------|--------|-------|--------|-------------|-------|------|-------|-------|------|-----|-----------|------------------|-----------------|-----------|------|---------|---------|
| | | 15 (57) | 30 (114) | 45 (170) | 60 (227) | 75 (284) | 95 (360) | 125 (473) | 150 (568) | 175 (662) | 185 (700) | 200 (757) | 250 (946) | 275 (1041) | 300 (1136) | 325 (1230) | 350 (1325) | | | Rigid | Swivel | Free Swivel | | Long | Short | Twist | Ball | Tab | Horseshoe | Spinning Plastic | Molded Urethane | Cut Metal | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | TYPE | LENGTH | |
| 1" | 100 (6.89) | • | • | • | • | | | | | | | | | | | | | | S | | | | | | | | | | | | | | | | |
| | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.5" | 100 (6.89) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 100 (6.89) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 50 (3.45) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 75 (5.17) | | | | | | | | | | | | | | | | S | | | | | | | | | | | | | | | | | | 4000-16 |
| | 100 (6.89) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 50 (3.45) | | | | | | | | | | | | | | | | S | O | | | | | | | | | | | | | | | | | 4000-20 |
| | 75 (5.17) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 (6.89) | | | | | | | | | | | | | | | | S | O | S | O | | | | | | | | | | | | | | | 4000-26 | |



Chief Nozzles

