

Select-O-Matic®

Pressure-regulating Select-O-Matic® nozzles automatically adjust to fluctuating water flow to maintain effective pressure and a consistent fire stream in all flow ranges. Our patented, completely unobstructed waterway allows more gpm at lower pressures than any competitive brand. All models flush easily without shutting down and provide constant flow on either fog or straight stream, making them ideal for the application of AFFF foam. Corrosion resistant; no lubrication required.



British Standard Parallel Pipe (BSPP) and British Instantaneous (BS336) base options available.

HANDLINE NOZZLES



SELECT-O-MATIC®

HANDLINE NOZZLES

1-7

Base Size	FLOW RANGES	PRESSURE	BASE					HANDLE		TEETH		MODEL
	GPM (LPM)		PSI (BAR)	TYPE			LENGTH		Tab	Horseshoe	Spinning	
		Rigid		Swivel	Free Swivel	Long	Short					
1"	10-75 (38-284)	100 (6.89)		s						s		TSM-3F
	60-125 (227-475)	100 (6.89)	o	s						s	o	TSM-10F
1.5"	60-200 (227-757)	75 (5.17)	o	s						s		TSM-20FLP
		100 (6.89)	o	s						s	o	TSM-20F
	75-325 (284-1230)	75 (5.17)	o	s						s	o	TSM-30FLP
		100 (6.89)	o	s						s	o	TSM-30F
2.5"	75-325 (284-1230)	100 (6.89)		s						s	o	DTSM-30F

Select-O-Matic Tips



1"	10-75 (38-284)	100 (6.89)	o		s			s	o	s		SM-3F
	60-125 (227-475)	100 (6.89)	o	s	o			o	s	s	o	SM-10F
1.5"	60-200 (227-757)	75 (5.17)	o	s	o			o	s	s		SM-20FLP
		100 (6.89)	o	s	o			o	s	s	o	SM-20F
	75-325 (284-1230)	75 (5.17)	o	s	o			o	s	s	o	SM-30FLP
		100 (6.89)	o	s	o			o	s	s	o	SM-30F
2.5"	75-325 (284-1230)	75 (5.17)		s	o	s	o	o	s	s	o	DSM-30FLP
		100 (6.89)		s	o	s	o	o	s	s	o	DSM-30F

Select-O-Matic Nozzles









1"	10-75 (38-284)	100 (6.89)	o		s			s	o	s		SM-3FG
	60-125 (227-475)	100 (6.89)	o	s	o			o	s	s	o	SM-10FG
1.5"	60-200 (227-757)	75 (5.17)	o	o	s			o	s	s		SM-20FGLP
		100 (6.89)	o	o	s			o	s	s	o	SM-20FG
	75-325 (284-1230)	75 (5.17)	o	o	s			o	s	s	o	SM-30FGLP
		100 (6.89)	o	o	s			o	s	s	o	SM-30FG
2.5"	75-325 (284-1230)	75 (5.17)		o	s	s	o	o	s	s	o	DSM-30FGLP
		100 (6.89)		s	o	s	o	o	s	s	o	DSM-30FG

Key: s = standard o = option

Figures depict general product types only and are not intended to be inclusive of all product features.



OPTIONS

HANDLES		MOLDED URETHANE TEETH	
TAB 	HORSESHOE 		
BASES		COLORS	
LONG 	SHORT 	 <p>Color options available for pistol grip, bumper, and handle. Glow available for bumper only. Retrofit kit available for Glow bumper. White bumper not available.</p>	
THREADS		<p>Select-O-Matic nozzle comes standard with a yellow bumper, chrome handle, and natural Elk-O-Lite® pistol grip.</p>	
<p>All nozzles are NHT unless otherwise specified. See index T-13 for optional base threads, including British instantaneous.</p>			

ADDITIONAL INFORMATION

PART NAME	PAGE #
Thread Information	T-13
Nozzle Flow Data	T-2
Hose and Nozzle Accessories	2-1
Foam Expansion Tubes	2-2