

HANDLINE NOZZLES



CELLAR / DISTRIBUTOR



CELLAR NOZZLE

SPECIFICATIONS	MODELS	
	LR	R
Base	1.5" F	2.5" F
GPM @ 100 PSI (6.89 BAR)	160 GPM (606 LPM)	350 GPM (1325 LPM)
Spray Diameter (Fog pattern)	20 Feet	55 Feet
Materials/Finish	Brass with chrome finish	



BRESNAN
DISTRIBUTOR
NOZZLE 193-6

SPECIFICATIONS	MODELS		
	193-6	193-6	193-9
Base	1.5" F	2.5" F	2.5" F
GPM @ 100 PSI (6.89 BAR)	140 GPM (530 LPM)	395 GPM (1495 LPM)	495 GPM (1874 LPM)
Spray Diameter (Fog pattern)	20 Feet	45 Feet	36 Feet
Materials/Finish	Brass with chrome finish		



BRESNAN
DISTRIBUTOR
NOZZLE 193-9



1.5" APPLICATOR FOR
CELLAR/BRESNAN
NOZZLE

SPECIFICATIONS	MODELS	
	A-1.5	A-2.5
Inlet	1.5" Free Swivel	2.5" Free Swivel
Outlet	1.5"	2.5"
Shut-off	Yes	No
Materials/Finish	Brass with chrome-plated finish	Elk-O-Lite® with red urethane enamel and anodized trim

HANDLINE NOZZLES

1-29



S-205-BAF

- For forestry use
- 1.0" rigid base in NHT or NPSH; 0.75" GHT available
- Available in 12 or 23 gpm (45 or 87 lpm)
- Twist shut-off
- For use with pressure of up to 600 psi (41.37 bar)
- Straight stream to fog
- Elk-O-Lite® construction



222-1.5

- Wat-R-Wall
- 1.5" free swivel inlet, no outlet
- 100 gpm (380 lpm) @ 100 psi (6.89 bar)
- Brass construction with chrome plating
- Length: 8"
- Width: 10"
- Height: 7.25"
- Weight: 8 lbs.



222-2.5

- Wat-R-Wall
- 2.5" free swivel inlet, 2.5" outlet with cap and chain
- 100 gpm (380 lpm) @ 100 psi (6.89 bar)
- Brass construction with chrome plating
- Length: 8.25"
- Width: 10"
- Height: 8.25"
- Weight: 11.5 lbs.