



WATER THIEFS

Water Thiefs

A Water Thief allows the fire professional to extend attack lines from a main supply line. Elkhart's selection of Water Thief options includes Storz connectors which, when combined with our unique free swiveling inlets and/or outlets, help prevent accidental uncoupling of larger diameter hose for increased safety.



INLET			FLOW THROUGH OUTLETS			THIEF OUTLETS			RELIEF VALVE	MATERIAL /TRIM			DIMENSIONS		MODEL	FIGURE
2.5" F*	Storz** (Swivel)		Twist-Lock	Gear Driven		Quarter Turn	Self-Locking Quarter Turn	Gated		Brass		Elk-O-Lite®	Length (Inches)	Weight (Lbs.)		
	4.0"	5.0"		2.5" M	4.0"					5.0"	Storz**					
						1.5" M (X2)	2.5" M (X2)	2.5" M (X2)								
s			s			•					•	10.5	10.8	BG-104A*	1	
s			s			•				•	•	10.5	23.5	BG-104	1	
	s	o		s	o		•		•		•	16.0	48.9	9743	2	
	s	o		s	o			•	•		•	16.0	46.9	9843	3	

KEY s = standard o = option

* Optional pressure gauges available

** Free swivel

FIGURE 1



BG-104 / BG-104A

- Flow through outlet (2.5") has acetal ball with adjustable neoprene seat and metal twist-lock handles
- Thief outlets (1.5") have self-adjusting UHMWPE seats and flexible urethane handles
- Leather carrying handles
- Optional pressure gauge

Fig. 1

FIGURE 2



9743

- Flow through Storz outlet has a gear actuated quarter turn 4" ball valve with aluminum ball and UHMWPE seat
- Thief outlets are 2.5" full flow, self-locking, Hydro-Loc®, quarter turn, acetal ball valves with neoprene seats
- Adjustable relief valve (75-250 psi)

Fig. 2

FIGURE 3



9843

- Flow through Storz outlet is a gear actuated quarter turn 4" ball valve with aluminum ball and UHMWPE seat
- Thief outlets are 2.5" gate valved outlets
- Adjustable relief valve (75-250 psi)

Fig. 3

OPTIONS

HANDLES

BG-104A options include:



LONG
(ELK-O-LITE®)



SHORT
(ELK-O-LITE®)



MOLDED URETHANE



KNOB

THREADS

All fireground connections are NHT T-13 for optional base threads.