



VALVED SIAMESE

APPLIANCES

Valved Siamese

Used to combine several hoselines into one — usually at the fire scene — a Siamese must be both reliable and intuitive to use. All the Siamese are finished in red urethane enamel; the Elk-O-Lite® versions feature hard anodized trim. As with all Elkhart products, years of dependable service are to be expected from an Elkhart Siamese.

4-5



INLETS	AVAILABLE OUTLETS		TYPE		HANDLE STYLE			VALVE	MATERIAL		DIMENSIONS		MODEL	FIGURE	
	Type	Size	1/4 Turn Ball Valve	X-86A Gate Valve	Crank	Self-Locking	Twist-Lock	Adjustable Relief Valve	Brass	Elk-O-Lite®	Length (Inches)	Weight (Lbs.)			
2.5" F (X2)	Female (Swivel)	2.5"	•				•			•	9.0	12.0	B-98A	1	
		4"	•				•			•	9.0	12.5	B-98A	1	
		4.5"	•					•			•	9.0	13.0	B-98A	1
		5"	•					•			•	9.0	13.6	B-98A	1
		6"	•					•			•	9.0	14.5	B-98A	1
	Storz (Free Swivel)	4"	•				•		s		•	13.3	26.3	9722	3
		5"	•				•		s		•	13.3	26.3	9722	3
2.5" F (X3)	Female (Swivel)	2.5"	•				•			•	10.5	18.2	B-99A	2	
		4"	•				•			•	10.5	18.6	B-99A	2	
		5"	•					•			•	10.5	19.7	B-99A	2
		6"	•					•			•	10.5	20.7	B-99A	2
	Storz (Free Swivel)	4"	•				•		s		•	16.0	30.6	9723	4
		5"	•				•		s		•	16.0	30.6	9723	4

Key: s = standard o = option

FIGURE 1



B-98A

- Apparatus mountable
- Built-in strainer
- Adjustable neoprene seats

Fig. 1

FIGURE 2



B-99A

- Apparatus mountable
- Built-in strainer
- Adjustable neoprene seats

Fig. 2

FIGURE 3



9722

- Full, flow Hydro-Loc® valves
- Adjustable relief valve (75-250 psi)

Fig. 3

FIGURE 4



9723

- Full, flow Hydro-Loc® valves
- Adjustable relief valve (75-250 psi)

Fig. 4

OPTIONS

THREADS

All fireground connections are NHT unless otherwise specified. See index T-13 for optional base threads.

ADDITIONAL INFORMATION

- All twist-locks feature metal knurled knobs.
- More Siamese options available. See page 4-3.