

Max. GPM (LPM)	CONTROL OPTIONS							MOUNTING OPTIONS					DEGREES OF TRAVEL		CERTIFICATIONS				MATERIAL OPTIONS			MONITOR SERIES	PAGE	
	Manual			Hydraulic	Electric	Wireless (RF)	EXM Tehcnology	Mobile			Stationary		Integral Ball Valve	Vertical	Horizontal	CE	Class I, Div 1	Class I, Div 2	FM Approved	Brass	Elk-O-Lite®			Stainless Steel
	Dual Hand-wheel	Single Hand-wheel	Tiller					Portable	Wheeled Cart	Apparatus	Fixed Installation	Elevated												
300 (1136)					•	•	•			•	•		135°	180°						•		Sidewinder® EXM UHP	5-10	
500 (1893)			•		•					•			135°	334°	•					•		Sidewinder® Electric	5-14	
								•					135°	360°						•		Sidewinder®	5-17	
700 (2650)					•	•	•			•	•		43°	40°	•					•		R.A.M.®	5-24	
													135°	350°						•		Sidewinder® EXM	5-2	
1000 (3785)	•		•								•		175°	360°					•			Manual Elevated	5-51	
								•					50°	90°					•			Portable Carts	5-56	
1250 (4732)					•	•	•			•	•		165°	350°					•			Cobra™ EXM 7200	5-4	
		•							•				95°	360°	•				•			Stinger® 2.0	5-27	
	•	•	•							•	•		135°	360°	•				•			Vulcan®	5-30	
										•	•		130°	360°	•				•			Stingray®	5-36	
	•		•							•	•		135°	360°	•			•	•			Copperhead	5-39	
			•							•	•		135°	360°	•			•	•			Python®	5-43	
		•	•							•	•		130°	360°	•			•	•			Hydrant Mount	5-49	
1500 (5678)					•	•	•			•	•		165°	350°					•			Cobra™ EXM 7250	5-4	
2000 (7571)					•					•	•		135°	347°	•				•	•		Scorpion® Electric	5-19	
	•		•							•	•		135°	360°	•				•			Scorpion®	5-22	
	•		•							•	•		135°	360°	•				•			Spit-Fire	5-33	
2500 (9463)					•	•	•			•	•		135°	350°					•			Scorpion® EXM	5-6	
										•	•		150°	360°	•			•		•		Giant Python	5-46	
3000 (11355)					•	•	•			•	•		135°	350°					•			SkyStream™ EXM	5-8	

DIMENSIONAL ABBREVIATIONS KEY:

- D.L. = Discharge Length
- H.H. = Handle Height
- H.S.R. = Handle Swing Radius
- M.H. = Monitor Height
- O.H. = Overall Height
- O.L. = Overall Length
- P.H. = Pivot Height
- P.R. = Pivot Radius
- W. = Width

ADDITIONAL INFORMATION

- Elkhart has trademarked the Elk-O-Lite® name for our proprietary aluminum alloy (cast alloy #356-A).

SYMBOLS



- Denotes flow or pressure rating

THREADS

- Throughout the monitor section, all threads – unless otherwise specified – are NHT. Additional thread information may be found on page T-13.