



SELECT-O-STREAM®

Select-O-Stream®

- Constant flow nozzle — straight stream, narrow fog (30°), or wide fog (90°)
- Flow efficient with a fully machined waterway for excellent stream quality
- Elk-O-Lite® nozzles are hard anodized with chrome-plated trim
- Corrosion resistant brass nozzles have a satin brass finish
- Large handles allow for easy stream pattern management
- Grease zerk for easy lubrication of tip threads
- Heavy-duty protective rubber bumper
- AFFF compatible
- Available FM rated

MASTER STREAM

6-11



Base Size	AVAILABLE STANDARD FLOW RATES GPM (LPM)				PATTERN CONTROL		TEETH	MATERIAL		CERT.	EFFECTIVE REACH (Ft.)		Weight (Lbs.)	MODEL	FIGURE
	350 (1325)	500 (1893)	750 (2839)	1000 (3785)	Direct Manual	Remote Control		Cut Metal	Brass		Elk-O-Lite®	At Lowest Flow			
	PSI (BAR) 100 (6.89)														
2.5"	•	•			•		•		•		150	173	5.5	CJ	1
	•	•			•		•	•	•		150	173	12.4	CJ-B	1
	•	•				•	•		•		150	173	7.3	CJ-RC	2
	•	•				•	•	•	•		150	173	14.5	CJ-B-RC	2
			•	•	•		•		•		238	263	6.5	CJN	1
			•	•	•		•	•	•		238	263	15.6	CJN-B	1
			•	•		•	•		•		238	263	8.5	CJN-RC	2
			•	•		•	•	•	•		238	263	17.8	CJN-B-RC	2
	•				•			•				150	10.8	IMS-350*	3
		•			•			•				173	10.8	IMS-500*	3
			•		•			•				238	13.1	IMS-750	4
				•	•			•				263	13.1	IMS-1000	4

* Wide Fog is 140°

SELECT-O-STREAM® CONFIGURATIONS

Figure 1	Figure 2
	
MANUAL <i>Fig. 1</i>	REMOTE <i>Fig. 2</i>
Figure 3	Figure 4
	
IMS-350 <i>Fig. 3</i>	IMS-1000 <i>Fig. 3</i>

OPTIONS
THREADS
<i>All nozzles are NHT unless otherwise specified. See index T-13 for optional base threads.</i>

Figures depict general product types only and are not intended to be inclusive of all product features.