



HOSE/NOZZLE ACCESSORIES & STANDPIPE

SWIVELING PLATE REDUCER - 101A

- 101A - 2.5" Female NHT x 1.5" Male NHT
- Hard anodized cast Elk-O-Lite® body
- Swivel Inlet
- Low profile knurling



SWIVELING BELL REDUCER - 102A

- 102A - 2.5" Female NHT x 1.5" Male NHT
- Hard anodized cast Elk-O-Lite® body
- Swivel Inlet
- Low profile knurling



INCREASER ADAPTER - 111A

- 111A - 1.5" Female NHT x 2.5" Male NHT
- Elk-O-Lite® construction with hard anodized finish
- Ideal for extend operations
- Low profile knurling



ELKHART STANDPIPE BAG

- Custom designed specifically for standpipe operations
- Handles made of seat belt webbing with seat belt buckle fasteners
- Made with durability in mind; reinforced stitching and reflective trim
- Internal and external pockets ideal for door chocks, pipe wrenches, wire brushes, adapters, etc.



STANDPIPE KIT

- (1) 228A Pressure Gauge
- (1) 105A Highrise Elbow
- (1) X-86A Gate Valve
- (2) T-464 Spanner Wrenches
- (1) Elkhart Standpipe Bag



228A



105A



X-86A



T-464





FLOW GAUGES & HOSE/NOZZLE ACCESSORIES

LINE GAUGE - 228A

- Fully guarded, shock resistant luminescent gauge
- Hard anodized cast Elk-O-Lite® body
- 228A – 1.5" 0-200 gauge with 1.5" free swivel inlet, 1.5" outlet, and 6" length
- 228A – 2.5" 0-200 gauge with 2.5" free swivel inlet, 2.5" outlet, color-coded zones, and 6.9" length



PIEZOMETER GAUGE - 227A

- Liquid-filled 0-300 psi gauge
- Elk-O-Lite® construction with hard anodized finish
- 227A – 1.5" (1.5" swivel inlet, 1.5" outlet, and 4.8" length)
- 227A – 2.5" (2.5" swivel inlet, 2.5" outlet, and 5.5" length)



PISTOL GRIP ADAPTER - PG

- For use with 1.5", 1.75" or 2" handline nozzles
- Elk-O-Lite® construction with hard anodized finish
- PG-S (1" free swivel inlet and waterway with 1" male outlet)
- PG (1.5" free swivel inlet and waterway with 1.5" female outlet)



DIRECT CONNECT ADAPTER - D-327

- 2.5" inlet
- 1.5" outlet
- Rigid base
- D-327 (Brass construction)
- D-327A (Elk-O-Lite® construction)



STANDPIPE FLOWMETER - 555A

- Compact design for high-rise kit applications
- Elk-O-Lite® construction with hard anodized finish
- Dual LED display - pressure and flow
- 45° swivel elbow
- 2.5" female swivel inlet / 2.5" threaded male discharge
- 250 GPM (946 LPM) maximum flow
- 250 PSI (17.2 BAR) max operating pressure
- Weight: 5 lb. 4oz. (2.38 kg)



PORTABLE FLOWMETER - EB-500

- Digital 0-500 gpm read-out display
- Flowmeter and flowtube-mounted paddlewheel flow sensor
- Low and high flow warnings
- Weather-tight PVC Pelican case includes: flowmeter, power switch, low battery indicator, rechargeable battery, AC charger/power supply, cable connections and cord storage space
- Weight: 17 lbs.
- Finish is hard anodized
- 2.5" flow tube (NST threads)



HOSE AND LADDER STRAP - 632

- Flexible woven nylon with brass ends
- Fits ladder rungs up to 1 1/8"
- Strap width 1"
- Length: 42"
- Less than 2 lbs.



HOSE CLAMP - 285

- For use with 1.5" – 3" hose, including double jacket 3"
- Unique jaw design allows for safer release of clamped hose
- Spring-loaded safety lock for closed position
- Detachable carrying handle
- ZA-27 aluminum construction
- Weight: 19 lbs.
- Length: 15"
- 285-MB – optional Elk-O-Lite® mountin bracket can be positioned vertically or horizontally





WRENCHES

T-464 – UNIVERSAL SPANNER

- Hammer head, window jimmy, gas cock slot, and hanger loop
- Fits up to a 3.5" rocker/lug pin coupling
- Elk-O-Lite® construction
- Length: 11.5"
- Weight: 0.5 lbs.



F-464 – FOLDING SPANNER

- One end is a spanner, the other is a window jimmy
- Fits up to a 3.5" rocker/lug pin coupling
- Clip ring
- Length: 10.4" (open) or 5.9" (folded)
- F-464A – Elk-O-Lite® construction (weight: 0.4 lbs.)
- F-464B – Brass construction (weight: 1.1 lbs.)



454 – ADJUSTABLE HYDRANT WRENCH

- Cast manganese bronze head with stainless steel handle
- Adjustable – fits up to 1.75" pentagon nut or 1.5" square nut
- Can be used as a spanner on 2.5" pin lug couplings
- Knurled handle
- Length: 18.0"
- Weight: 3.8 lbs.



S-454 – ADJUSTABLE HYDRANT WRENCH

- Cast manganese bronze head with stainless steel handle
- Adjustable – fits up to 1.75" pentagon nut or 1.5" square nut
- Can be used as a spanner on 2.5" pin lug couplings or rocker lug couplings from 2.5" to 5.0"
- Knurled handle
- Length: 16.8"
- Weight: 4.6 lbs.



S-454-S – ADJUSTABLE HYDRANT WRENCH

- Cast manganese bronze head with stainless steel handle
- Adjustable – fits up to 1.75" pentagon nut or 1.5" square nut
- Can be used as a spanner on 4.0" or 5.0" Storz couplings or rocker lug couplings from 2.5" to 5.0"
- Knurled handle
- Length: 17.3"
- Weight: 4.9 lbs.



469 – SPANNER WRENCH HOLDER

- Mounts vertically or horizontally on apparatus
- Holds two T-464 universal spanners
- Snap action release
- Elk-O-Lite® construction
- Length: 7.4"
- Weight: 1 lbs.
- Wrenches optional as kit



470 – HYDRANT AND SPANNER WRENCH HOLDER

- Mounts vertically or horizontally on apparatus
- Holds two T-464 universal spanners plus one hydrant wrench (454, S-454, or S-454-S)
- Snap action release
- Elk-O-Lite® construction
- Length: 10.0"
- Weight: 1.5 lbs.
- Wrenches optional as kit



HYDRANT HOUSE ACCESSORIES

630 – CROWBAR

- Constructed of steel and finished with red paint
- Length: Ranges from 47.5" to 49.25"
- Weight: 12 1/8 lbs.





ELKHART BRASS SPECIAL TOOLS



71251000 – SEAT WRENCH

- For seat adjustment and/or removal
- 1" or 1.5" nozzle/ball shut-off
- 1" waterway compatible



71252000 – SEAT WRENCH

- For seat adjustment and/or removal
- 1.75", 2" or 2.5" nozzle/ball shut-off
- 1.375" waterway compatible



SEAT WRENCH

- Specially designed to be used for seat removal/installation on 9786 or 9787 PIV
- 4.5" outlet compatible (01501001)
- 5" or 6" outlet compatible (01502001)



80642001 – WYE SEAT WRENCH

- For seat adjustment and/or removal on 1.5" ball valved wyes
- Hex end fits old style B-100, B-100L and BG-104
- Blade end fits old style B-100A, B-100-LA and BG-104A



80269001 – STEM WEB WRENCH

- Designed to hold the stem web (base) while removing and/or installing Master Stream heads
- Slotted end fits Select-O-Stream®, Select-O-Flow®, and Mystery® stem bases



80313001 – STEM WEB WRENCH

- Designed to hold stem web (base) while removing and/or installing handline nozzle stem heads
- Slotted end fits most of Elkhart's handline nozzle bases (except Select-O-Matics®)



71258000 – OPEN FACE 2" SPANNER WRENCH

- Seat adjustments and/or removal on 800 series and 2800 series apparatus valves
- Seat adjustments and/or removal on Elkhart's wyes, Siamese and water thieves (2.5 seat only)
- Removal and/or installation of stem heads on all Select-O-Matic® handline nozzles



80291001 – STEM HEAD WRENCH

- Designed to assist in removing and/or installing slotted stem heads
- Blade end fits slotted handline nozzle stems (except Select-O-Matics®)

71303001 – OPEN FACE 4" SPANNER WRENCH

- Removal and/or installation of stem heads on Master Stream nozzles (except X-Stream® series)
- Larger version of P/N 71258000

603 – TOOL KIT

- Seat wrenches (71251000 and 71252000)
- Open faced spanner wrench (71258000)
- Stem head wrenches (80291001 and 80313001)
- Wye seat wrench (80642001)