
























MASTER STREAM
























SELECTOR GUIDE

MASTER STREAM

6-1

		AVAILABLE BASE			PRODUCT	DESCRIPTION	MATERIAL			"QUICK-KEY"
		1.5	2.5	3.5			Brass	Composite	Elk-O-Lite®	
FIXED	5000E	•			 <p><i>Page 6-3</i></p>	<ul style="list-style-type: none"> Combination nozzle 12 or 24 VDC enclosed and sealed motor 		•	 	
		Available GPM (LPM) 15-475 (57-1798)								
AUTOMATIC	SIM-10FE	•			 <p><i>Page 6-3</i></p>	<ul style="list-style-type: none"> Simplifies fireground hydraulics Maintains effective flow stream 12 or 24 VDC enclosed and sealed motor 		•	 	
		Available GPM (LPM) 20-120 (76-454)								
FIXED/SELECTABLE	R.A.N.		•		 <p><i>Page 6-5</i></p>	<ul style="list-style-type: none"> Designed for use with R.A.M. Integral stream shaper 1/4 turn stream adjustment Optional oscillating configuration available 		•	  	
		Available GPM (LPM) 250-500 (946-1893)								
AUTOMATIC	X-STREAM®		•	•	 <p><i>Page 6-6</i></p>	<ul style="list-style-type: none"> Simplifies fireground hydraulics Maintains effective flow stream Calibrated at lower pressures - 75 & 80 PSI 		•	     	
		Available GPM (LPM) 300-2000 (1136-7571)								
SELECTABLE	6000	•	•		 <p><i>Page 6-9</i></p>	<ul style="list-style-type: none"> Designed for use with Sidewinder EXM Maintains effective flow stream Motor enclosed and sealed 		•	 	
		Available GPM (LPM) 15-700 (60-2700)								
FOAM EXPANSION TUBES			•	•	 <p><i>Page 6-10</i></p>	<ul style="list-style-type: none"> Quick-snap connection Composite or metal construction 		•	 	
		Available GPM (LPM)								

	AVAILABLE BASE			PRODUCT	DESCRIPTION	MATERIAL			"QUICK-KEY"	
	1.5	2.5	3.5			Brass	Composite	Elk-O-Lite®	Hand	Electrical
FIXED	SELECT-O-STREAM®			 <p>Page 6-11</p>	<ul style="list-style-type: none"> Fully machined waterway for excellent stream quality Large handles for easy stream pattern management Constant Flow Nozzle 	•	•	•	   	
	•	•	•							Available GPM (LPM) 350-1000 (1325-3785)
SELECTABLE	SELECT-O-FLOW®			 <p>Page 6-13</p>	<ul style="list-style-type: none"> Large handles for easy stream pattern management Operator set flow and stream Selectable Flow Nozzle 	•	•	•	  	
	•	•	•							Available GPM (LPM) 300-1250 (1136-4732)
FIXED	MYSTERY			 <p>Page 6-14</p>	<ul style="list-style-type: none"> Created for Industrial applications Large handles for easy stream pattern management Low maintenance 	•	•	•	  	
	•	•	•							Available GPM (LPM) 350-2000 (1325-7571)
AUTOMATIC/FIXED	SELF-EDUCTING			 <p>Page 6-15</p>	<ul style="list-style-type: none"> Self-educing Class A and B foam 1/2%, 1%, 3%, or 6% proportioning Field-adjustable foam proportioning 	•	•	•	    	
	•	•	•							Available GPM (LPM) 350-2000 (1325-7571)
ADJUSTABLE/FIXED	FIXED SYSTEM			 <p>Page 6-19</p>	<ul style="list-style-type: none"> Designed for use in fixed system applications Field-adjustable flow rate and fog pattern up to 120° 	•	•	•		
	•	•	•							Available GPM (LPM) 5-1000 (20-3780)

KEY:

											
Electrical Operation	Manual Operation	Remote Control Operation	Hydraulic Operation	Hazardous Location	Self-Educting Foam	Foam Compatible	Underwriters Laboratories	Twist Shut-off Available	Low Pressure Available	Conformity European	FM APPROVED Factory Mutual