

ADAPTERS, CAPS & PLUGS



CAPS & PLUGS


ADAPTERS, CAPS & PLUGS

11-1

Cap/Plug	Size (Inches)	TYPE				MATERIAL/FINISH			CHAIN		DIMENSION		MODEL	FIGURE
		Long Handle	Pin	Rocker	Storz	Brass		Elk-O-Lite®	9"	16"	Length (Inches)	Weight (Lbs.)		
						Cast brass	Chrome-plated							
Cap	1.0			•		s	o		s	o	1.125	0.4	310	1
				•				s	s	o	1.125	0.2	310A	1
	1.5		•			s	o		s		1.125	0.7	310	1
				•		s	o		s	o	1.125	0.5	310	1
	2.5	•				s	o		s	o	1.5	0.4	310A	1
			•			s	o		s		1.5	2.5	310LH	3
	3.0			•		s	o		s	o	1.5	1.8	310	1
				•		s	o		s	o	1.5	1.3	310	1
	4.0				•					*	2.75	2.4	310 Storz	2
		•				s	o		s	o	1.875	4.1	310	1
	4.5			•							1.75	4.5	310LH	3
		•				s	o		s	o	2.125	5.5	310	1
5.0				•						2.125	8.0	310LH	3	
	•				s	o			*	2.625	3.5	310 Storz	2	
6.0										1.5	6.8	310LH	3	
	•				s	o				1.625	7.5	310LH	3	
Plug	1.5		•			s	o				1.75	1.1	311	4
				•		s	o				1.75	1.1	311	4
	2.5			•		s	o				2.0	1.1	311	4
			•			s	o				2.125	2.2	311	4
	3.0			•				s			2.25	0.8	311A	4
		•				s	o				0.875	0.3	313	5

KEY s = standard o = option
 * Storz option comes with an 16" stainless steel cable.

Figure 1




CAP

- Available with 9" or 16" chain
- 175 PSI max rated pressure

Fig. 1

Figure 2




STORZ CAP

- 16" stainless steel cable

Fig. 2

Figure 3




LONG HANDLE CAP

- Conforms to NFPA 1901 for 500 psi service
- No chain

Fig. 3

Figure 4




PLUG

- Available with 9" chain

Fig. 4

Figure 5



SPANNER LUG PLUG

- "Easy-off" swivel cap
- No chain
- U.L. Listed

Fig. 5

OPTIONS

THREADS

Where noted as hose thread, NHT is standard. See index T-13 for optional base threads.

Figures depict general product types only and are not intended to be inclusive of all product features.

Adapters

In the over 100 years Elkhart has been a fire service manufacturer, we have created a wide assortment of standardized adapters to meet the varied needs of the fire industry. This extensive selection includes thread adapters to suit any need — whether for a male to female; a suction adapter with built-in strainer, NHT, NPT or custom order; or even for a universal adapter — you can find the perfect fit here.

- A selection of rocker lug and pin lug options
- Aluminum, Brass, and Chrome finishes available

Adapter
Mo. M-327



High Rise Elbow
Mo. 105A



Several material options — lightweight Elk-O-Lite® or durable cast brass (including some with chrome-plated finish)

ADAPTERS, CAPS & PLUGS



HOSE TO HOSE ADAPTERS

ADAPTERS, CAPS & PLUGS

11-3

What kind of adapter do you need?																							
Step 1: Select Material	Step 2: Choose Connection Type (Inlet to Outlet)	Step 3: Determine Gender (Inlet to Outlet)	Step 4: Select from available options														Step 5: Pick Model Model	Figure					
			Inlet	Size (Inches)											Construction				Type				
				1	1.5	2	2.5	3	3.5	4	4.5	5	6	Solid	Swivel	Hex			Internal Lug	Long Handle	Rocker		
Brass	Hose Thread to Hose Thread	NHT (M) to NHT (F)	1	•											•				s	A-327	9		
			1.5		•										•					s	D-327	8	
			1.5	•		•										•					s	A-327*	9
			1.5			•										•	•		s		s	S-327	11
			2				•									•					s	A-327	9
			2.5	•			•	•								•					s	S-327	11
			2.5				•	•								•	•		s		s	105	3
			2.5				•	•								•					s	A-327	9
			3				•	•								•					s	S-327	11
			3				•	•								•	•		s		s	A-327	9
			3				•	•								•					s	S-327	11
			3				•	•								•					s	105	3
		3.5								•						•				s			
		1.5	•	•		•										•					s	A-327	9
		2.5		•												•					s	D-327	8
		2.5		•	•		•	•								•					s	A-327*	9
		2.5		•			•	•								•	•		s		s	S-327	11
		2.5		•			•	•								•					s	105	3
		3					•	•								•					s	A-327	9
		3					•	•								•	•		s		s	S-327	11
		3					•	•								•					s	105	3
		3.5								•						•					s		
		NHT (M) to NHT (M)	1.5		•											•					s	M-327	6
		NHT (F) to NHT (F)	1.5		•											•					s	F-327	1
	2.5				•									•					s	F-327	1		
	3							•						•					s	S-319	3		
	4.5									•	•	•					s						
Aluminum	Hose Thread to Hose Thread	NHT (M) to NHT (F)	1.5			•								•					s	D-327A	7		
			1.5		•										•					s	A-327A	10	
		2.5				•									•					s	A-327A	10	
		NHT (F) to NHT (M)	1.5	•											•					s	D-327A	7	
		2.5		•			•								•					s	M-327A	4	
		2.5		•											•					s	M-327ABI	5	
		NHT (M) to NHT (M)	1.5		•										•					s	F-327A	2	
		2.5					•								•					s			

Key s = standard o = option

* A327 has optional pin lug and chrome finish in the 2.5F by 1.5M/1.5M by 2.5F size.

OPTIONS

THREADS

NHT can also be called NST. See T-13 for optional threads.

MEASUREMENTS


Length measurements shown on page T-15.

UNIVERSAL ADAPTER












435

- Cast brass construction with chrome-plated finish
- Adapts any 2.5" hose thread to 2.5" NHT
- Positive ratchet lock with thumb release
- Weight: 6.42 lbs.

	FEMALE/FEMALE	MALE/MALE	MIXED
Figure 1	 <p>F-327</p> <ul style="list-style-type: none"> • Double swivel female • Cast brass finish (chrome optional) <p><i>Fig. 1</i></p>	 <p>M-327A</p> <ul style="list-style-type: none"> • Double male <p><i>Fig. 4</i></p>	 <p>D-327A</p> <ul style="list-style-type: none"> • Direct connect adapter <p><i>Fig. 7</i></p>
Figure 2	 <p>F-327A</p> <ul style="list-style-type: none"> • Double swivel female <p><i>Fig. 2</i></p>	 <p>M-327ABI</p> <ul style="list-style-type: none"> • Double male British Instantaneous <p><i>Fig. 5</i></p>	 <p>D-327</p> <ul style="list-style-type: none"> • Direct connect adapter • Chrome finish (cast brass optional) <p><i>Fig. 8</i></p>
Figure 3	 <p>105</p> <ul style="list-style-type: none"> • 45° discharge elbow • Female rocker lug • Chrome finish <p><i>Fig. 3</i></p>	 <p>M-327</p> <ul style="list-style-type: none"> • Double male • Cast brass finish (chrome optional) <p><i>Fig. 6</i></p>	 <p>A-327</p> <ul style="list-style-type: none"> • Female rocker lug <p><i>Fig. 9</i></p>
<p>ADDITIONAL INFORMATION</p> <p><i>When ordering, specify: model number; inlet size, gender, and thread; outlet size, gender, and thread; as well as any optional type or finish information.</i></p>			
<p>105A High Rise Elbow</p> <ul style="list-style-type: none"> • 45° drain elbow • 2.5" Female free swivel • 2.5" Male discharge • Integrated Model 114 drain valve • 250 GPM flow • 200 PSI operating pressure • 1 lb. 3 oz. 			
Figure 10			 <p>A-327A</p> <ul style="list-style-type: none"> • Female rocker lug <p><i>Fig. 10</i></p>
Figure 11			 <p>S-327</p> <ul style="list-style-type: none"> • Internal lug body • External female rocker lug • Cast brass finish (chrome optional) <p><i>Fig. 11</i></p>

ADAPTERS, CAPS & PLUGS

HOSE TO PIPE / PIPE TO HOSE ADAPTERS

	FEMALE/FEMALE	MALE/MALE	MIXED		
Figure 14	 <p>160</p> <ul style="list-style-type: none"> • Swivel female to female • Cast brass finish (chrome optional) <p><i>Fig. 14</i></p>	Figure 17	 <p>306</p> <ul style="list-style-type: none"> • Double male • Cast brass finish (chrome optional) <p><i>Fig. 17</i></p>	Figure 18	 <p>307</p> <ul style="list-style-type: none"> • Cast brass finish (chrome optional) <p><i>Fig. 18</i></p>
Figure 15	 <p>3060</p> <ul style="list-style-type: none"> • Double female • Cast brass finish (chrome optional) <p><i>Fig. 15</i></p>		Figure 19	 <p>418</p> <ul style="list-style-type: none"> • Suction adapter • Removable strainer • Chrome finish <p><i>Fig. 19</i></p>	
Figure 16	 <p>419</p> <ul style="list-style-type: none"> • Swivel female to female suction adapter • Built-in strainer • Chrome finish <p><i>Fig. 16</i></p>		Figure 20	 <p>418-L</p> <ul style="list-style-type: none"> • Long discharge adapter • Chrome finish <p><i>Fig. 20</i></p>	
			Figure 21	 <p>418-S</p> <ul style="list-style-type: none"> • Short discharge adapter • Chrome finish <p><i>Fig. 21</i></p>	
			Figure 22	 <p>418-SA</p> <ul style="list-style-type: none"> • Short discharge adapter • Female rocker lug <p><i>Fig. 22</i></p>	

ADDITIONAL INFORMATION

When ordering, specify: model number; inlet size, gender and thread; outlet size, gender and thread; as well as any optional type or finish information.