

CERTIFICATE OF COMPLIANCE

Certificate Number 20150727-EX1394
Report Reference EX1394-19570218
Issue Date 2015-JULY-27

Issued to: ELKHART BRASS MFG CO INC
1302 W BEARDSLEY AVE, PO BOX 1127,
ELKHART IN 46515


**This is to certify that
representative samples of** NOZZLES, SPRAY HOSE, PORTABLE
See Next page for Models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 401 - Portable Spray Hose Nozzles for Fire-Protection
Service

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Listing Mark should be considered as being covered by UL's
Listing and Follow-Up Service.

The UL Listing Mark generally includes the following elements: the symbol UL in a circle:  with the
word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category
name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20150727-EX1394
Report Reference EX1394-19570218
Issue Date 2015-JULY-27

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Adjustable Nozzles – For Classes A, B, and C fires. For use with rubber-lined or unlined fire hose. A suffix letter "B" may be used to denote a rubber bumper.

Model No.	Size In.	Nozzle Pressure psi	Discharge GPM Wide Open
L-205-EB60	1-1/2	100	65
L-205-EB95	1-1/2	100	102
L-205-EB125	1-1/2	100	135
NSL	1-1/2	100	92

Use of these nozzles not likely to prove hazardous when held at distance in excess of 10 ft from live electrical apparatus and circuits involving voltages not in excess of 250,000.

Adjustable Nozzles– For Classes A and B fires only. For use with rubber-lined or unlined fire hose. A suffix letter "B" may be used to denote a rubber bumper. The Models S-205-B, 205-B(170), D205-B(170), 205-B(250) and D205-B(250) are for use with rubber-lined fire hose only.

Model No.	Size In.	Nozzle Pressure psi	Discharge GPM Wide Open
205-B(170)	1-1/2	100	171
D205-B(170)	2-1/2	100	171
205-B(250)	1-1/2	100	275
D205-B(250)	2-1/2	100	275
L-205-B40	1-1/2	100	39
L-205-B60	1-1/2	100	61
L-205-B95	1-1/2	100	100
L-205-B125	1-1/2	100	135
L-206T	1-1/2	100	120
S-205B-12GPM	1	100	12
S-205-B-23GPM	1	100	28

Use of solid stream from nozzle around live electrical apparatus and circuits may involve serious accident hazard, and these nozzles, therefore, are not recommended for use in Class C fires.



William R. Carney, Director, North American Certification Programs
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

