



USE ONE

12	62165001-B	STEM-NOZZLE (1250-GPM)	1
12	62164001-B	STEM-NOZZLE (1500-GPM)	1
12	62163001-B	STEM-NOZZLE (1750-GPM)	1
12	62162001-B	STEM-NOZZLE (2000-GPM)	1

26	28016000-A	ELBOW-90° X 90° (BRASS)	2
25	28150000-A	ELBOW-PIPE (BRASS) PH# 40812-B	4
24	67077000-A	TEE (WALLET) 1/2"-N.P.T. BRASS	2
23	70036000-A	VALVE (METERING) BRASS	1
22	67102001-A	TUBE (HYDRAULIC)	2
21	32112000-A	FITTING-HYDRAULIC	2
20	10728000-A	ADAPTER-MALE X MALE	2
19	61074000-A	SCREW-CAP (STNLS STL)	4
18	16559001-A	BRACKET (ANGLE)	2
17	47544000	NUT-JAM (STNLS STL)	2
16	66337002-C	TIP-NOZZLE	1
15	57423000	RING-O (AS-568-242)	1
14	57316000	RING-O (AS-568-242)	1
13	17140001-C	BODY (BASE) NOZZLE	1
11	63398001-A	BASE-STEM (WEB)	1
10	47474000-A	NUT-JAM (STNLS STL)	1
9	23035000-A	CYLINDER-POWER (HYD)	2
8	33243000	GASKET-RUBBER	1
7	63781000-A	SCREW-CAP (STNLS STL)	4
6	57313000	RING-O (AS-568-239)	1
5	11548001-A	ADAPTER-BODY (3.5" B/G)	1
4	61222000-A	SCREW-SET (BRASS)	1
3	15016000-A	BALLS- .187 Ø BRASS	7
2	33186000	GASKET-RUBBER (NET)	1
1	63311002-A	SHIVEL-B/G 2-R/L (3.5"NHT)	1

NOZZLE FUNCTION	HYD. PORT
FOG	3B 3A
STRT	3A 3B

NOTE #1 SECURE THD W/ LOC-TITE #262 (RED)

NO.	PART NO.	PART NAME	REQ.
<b>ELKHART BRASS MFG. CO., INC.</b> ELKHART, INDIANA			
<b>2000-GPM CONSTANT FLOW NOZZLE</b>			
DRN BY	R MILLER	SCALE	FULL
DATE		DATE	8/26/93
DRW BY	RM	DWG. NO.	
STANDARD TOLERANCE			D
CADAM			

<b>PART NO.</b>	<b>QUANTITY PER UNIT</b>	<b>DESCRIPTION</b>
63311	1	3.5" R/L Swivel
33186	1	Rubber Gasket, 3.5"
15016	71	.187" Diameter Brass Ball
61222	1	Set Screw
11548	1	Body Adapter (B/G)
57313	1	O-Ring
63781	4	Cap Screw (#8-32 X .375" Lg)
33243	1	Rubber Gasket
23030	2	Hydraulic Cylinder, O/S (Pre '94)
23035	2	Hydraulic Cylinder, N/S
47474	1	Jam Nut (.500-20)
63398	1	Stem Base (Web)
62065	1	Stem Head (2000 gpm), O/S (Pre '93)
62162	1	Stem Head (2000 gpm), N/S
17104	1	Nozzle Body, O/S (Pre '93)
17140	1	Nozzle Body, N/S
57316	1	O-Ring
57423	1	O-Ring
66337	1	Nozzle Tip
47544	2	Jam Nut (.250-28)
16559	2	Angle, Bracket
61074	4	Cap Screw (#8-32 X 1.0" Lg)
10728	2	Adapter (.125 NPT M X .437-20 JIC 37°)
32112	2	Hydraulic Fitting (45°), .125 NPT Fe B/E
67102	2	Hydraulic Tube
70036	1	Metering Valve
67077	2	Tee (Male), .125 NPT A/E
28150	4	Elbow (90°), .125 NPT Fe X .250 OD
28016	2	Elbow (90°), .125 NPT Ma B/E
<b>OPTIONAL STEMS</b>		
62073	1	Stem Head (1750 gpm), O/S (Pre '93)
62163	1	Stem Head (1750 gpm), N/S
62066	1	Stem Head (1500 gpm), O/S (Pre '93)
62164	1	Stem Head (1500 gpm), N/S
62067	1	Stem Head (1250 gpm), O/S (Pre '93)
62165	1	Stem Head (1250 gpm), N/S