

Stingray®

- Flow efficient 3" waterway allows for flows up to 1250 gpm
- All construction features designed to minimize maintenance needs
 - Choice of corrosion resistant brass or lightweight Elk-O-Lite® construction
 - Fully enclosed gearcase with stainless steel worm
 - Bronze balls in all swivel joints
 - Grease zerks for easy lubrication
- Flexible installation options include numerous base options and a hydrant mounting choice
- Compact size — 16" high or 21" high — is extremely versatile, allowing the monitor to serve a variety of real-world needs
- Built-in shut-off capabilities (with the Stingray® IV) from a full flow 3" ball valve



Vaned elbow

Horizontal twist lock

Stingray
Mo. 8393IV
(Nozzle sold separately)

200
PSI

1250
GPM








STINGRAY®

MONITORS

SPECIFICATIONS			
Max. GPM (LPM)	1250 (4732)		
Inlets	Sizes		Types
	4"	150# ANSI Flange	
	3"	150# ANSI Flange	NPT (F)
Outlet Size	2.5" NHT		
Control	Single hand-wheel		
Material/Finish	Brass or Elk-O-Lite® with red urethane enamel		
Friction Loss	27 psi at 1250 gpm		
	17 psi at 1000 gpm		
	9 psi at 750 gpm		
Travel	V -60° to +90° (150°)		
	H 360° (continuous)		
Weight	Varies (See specification chart)		
Ratings and Certifications	CE and FM Approved		

KEY CONFIGURATIONS (ACCESSORIES)		
 STINGRAY® (2)	 PRESSURE GAUGE (3)	 BALL VALVE (4)

NOTE: Ball valve cannot be ordered separate from monitor as a stand alone part.

Stingray® Selector Guide

INLET SIZES / TYPES			OUTLET SIZE	VERTICAL TRAVEL		INTEGRAL COMPONENTS		MATERIALS			CERTIFICATIONS		DIMENSIONS				ILLUSTRATION	MODEL
NPT	150 # ANSI Flange		2.5"	-60° to +70°	-60° to +90°	Ball Valve	Pressure Gauge	Brass	Elk-O-Lite®	CE	FM Approved	Width (In.)	Depth (In.)	Height (In.)	Weight (Lbs.)			
3"	3"	4"		NHT	(130°)											(150°)	3"	
o	o	s	•	o	s	s		•		•	•	14.75	15.75	20.375	68.25	1	8393IV	
o	o	s	•	s	o		o	•		•	•	14.75	15.75	15.75	47.5	2	8393	
o	o	s	•	s	o		o		•	•	•	14.75	15.75	15.75	16.0	2	8393-A	
						4	3										Illustration	

KEY s = standard o = option

Recommended Products

SM-1000HF – SELF-EDUCTING	IMS-500 SELECT-O-STREAM®	J-MYSTERY®	282B STREAM SHAPER	181-SMOOTH BORE	SM-1250B X-STREAM®	WPO-2000
						
Page 6-16	Page 6-12	Page 6-14	Page 1-27	Page 1-26	Page 6-7	Page 5-53

Components & Options Chart

COMPONENTS & OPTIONS	ILLUSTRATION	MODEL
Companion Flange Kits	3" 150# ANSI steel flange with bolts and gaskets	81315001
	4" 150# ANSI steel flange with bolts and gaskets	81317001

Product Highlights

Our Stingray® IV features a 3" integral quarter-turn full flow ball valve. The integrated valve eliminates the need for a separate valve; it is both easier to install and more reliable than a separate wafer valve. The benefits of the integrated valve include:

- 1) better total monitor efficiency as the friction loss between the traditional separate monitor and valve is reduced*
- 2) a turn-key package created by integrating the valve into the monitor*

Highlights of the Stingray® IV valve include:

- Hydraulically balanced acetal ball*
- Teflon impregnated seats*
- Full flow ball valve*

ADDITIONAL INFORMATION

- All flanges specified with the monitor are flat. Raised flanges are available with some inlet sizes. Please inquire with our sales staff.*
- Marine Brass (85-5-5-5) construction is available on some models. Please inquire with our sales staff.*
- Technical Data on monitor performance may be found on page T-11.*
- The Stingray® is also available in a portable cart version. Please see page 5-56 for details.*
- The Stingray® is also available in a hydrant mount version. Please see page 5-50 for details.*